



# SECURE-TECH

DETENTION ELECTRONIC SYSTEMS

ETECH CONTROLS CORPORATION - MANUFACTURER  
4051 ALVIS COURT #3, ROCKLIN, CALIFORNIA, USA 95677  
TEL (916) 630-1300 • FAX (916) 630-1100 • FREE (800) 800-2523

## TELEPHONE VISITATION INTERCOM

### TELEPHONE HANDSETS, WALL PLATES, BASES, AND BACKBOXES

#### FEATURES:

- FOR VISITATION OR INTERCOM SYSTEMS
- 500 SERIES HANDSETS W/SEALED CAPS OR SET-SCREWS OPTIONAL
- CARBON OR DYNAMIC TRANSMITTERS WITH OR WITHOUT HOOKSWITCH
- DETENTION GRADE ASSEMBLY ARMORED CABLE (CUSTOM LENGTHS) EXCLUSIVE CABLE MOUNTING BLOCK STEEL LANYARD
- STAINLESS STEEL WALL PLATES
- CHROME HANGERS - DPDT OR 4PDT
- HANDSET POWER AMPLIFIED OPTION
- RETRO SURFACE SECURITY BACKBOXES
- 2 YEAR WARRANTY



#### FUNCTIONAL DESCRIPTION:

For use in locations where privacy is required. Industry standard 500 series handsets are available in various styles with a complete array of functions and bases:

- Handset with chrome hanger and hookswitch assembly mounted on a stainless steel plate
- Handset with desk base (500/2500 series)
- Handset adjustable power amp receiver (-P)
- Handset Push-To-Talk button (-T)

Standard - 2-device stainless steel wall mount plate (W), carbon (C) transmitter, chrome hanger, DPDT hookswitch, tamper resistant cable mounting block. Other transmitters available are Dynamic (D) and Electret (E). Available cables lengths are 18", standard 32", 48" or 54" armored cables, all with steel LANYARD strain relief and standard 6, 9 or 15 foot coiled cords. Custom armored cable lengths from 10" to 9' (handicap). Beige is standard color. Black (-BK), Green (G) and red (-RD) are available. Heavy duty coiled cords are available.

Hookswitches may be deleted when remotely controlled - (add "-E"). for significant savings.

Surface mounted steel security backboxes are available in various designs, including a 10 gauge steel beveled safety type (TBB-2/11B).

The CTI-1 cross-talk isolation module may be used to isolate a unit of two or three wallsets from cross-talk interference or leakage with other units. Eliminates home run wiring. Installs in either wallset backbox. Power supply requirement is 20 ma per unit @12-18 VAC/VDC.

#### MODELS:

##### **ALL ARMORED CABLES CONTAIN A STEEL LANYARD**

Wall mount SST plate, 18", 32", 48" or 54" armored cable

WC2-32AMCL Carbon xmtr, 2 gang, armor cable

WD2-32AMCL Dynamic xmtr, 2 gang, armor cable

Replace the 2 with a 4 for a 4 gang SST plate

Wall mount SST plate, 6', 9' OR 15" coiled cord

WC2-6CC Carbon xmtr, 2 gang, 6' cord

WD2-15CC Dynamic xmtr, 2 gang, 15' cord

Replace the 2 with a 4 for a 4 gang SST plate

CC2-32AMCL CLIP HANGER, snaps handset in cradle in wall, overhead or sloped panel installations.

Desk mount 500/2500 base, coiled cord

DC1-6CC Carbon xmtr, 6' cord

DD1-6CC-SP-T Dynamic xmtr, 6' cord, base speaker, handset push-to-talk

Handset only

HD9-32AMCL Dynamic xmtr, armor cable

HC9-6CC-CDC\* Carbon xmtr, 6' cord, CDC design

WP2-CDC\* Wall plate, RJ-11 jack, CDC design

\*Complies with the California Department of Corrections specifications for prisoner side visitor telephone system

Tamperproof surface mount steel security backboxes

TBB-2/10	10 gauge, 5.25" (133.3mm) square x 3" D (72.4mm), Steel
TBB-2/11B	11 gauge, 8.5" (215.9mm) square x 1.63" D (41.28mm), prime finish
TBB-2/14	14 gauge, 5.25" (133.3mm) square x 3" D (72.4mm), black

Cross-talk isolation circuit

CTI-1 Isolates up to three handsets

Detention grade handset cable mounting block

CMB Aluminum, 1" (25.4mm) square x 0.63" D (15.88mm), natural

